

<u>Product</u>	<u>Temperature</u>	<u>Pressure</u>	<u>Speed</u>	<u>pH</u>	<u>Services</u>	<u>Applications</u>
<u>Excelite 82</u>	120 ⁰ C	14 Mpa (140 bar)	2 m/s	5 - 11	Fuel, hydraulic and mineral-based oils, water	Slow rotary, reciprocating and static. Valves, fuel transfer and other pumps
<u>Hydrapack 7300</u>	120 ⁰ C	28 Mpa (280 bar)	2 m/s	5 - 9	Hydraulic oils	Reciprocating rods, accumulators, hydraulic rams and presses.
<u>Serpent AX12</u>	200 ⁰ C	7 Mpa (70 bar)	2 m/s	5 - 11	Particularly suitable for steam.	Slow rotary and reciprocating rods, bilge pumps, cargo pumps, boiler feed pumps, auxiliary steam services, compressors.
<u>Serpent C 80</u>	120 ⁰ C	7 Mpa (70 bar)	1 m/s	5 - 11	Hot and cold water, low- pressure steam, ammonia and brine	Reciprocating and static. Reciprocating compressors, elbow glands, cylinder jacket expansion glands, refrigeration machinery.
<u>Springbok 51</u>	120 ⁰ C	21 Mpa (210 bar)	2 m/s	5 - 9	Oil and water.	Reciprocating and hydraulic applications, accumulators, presses and extruders.
<u>Vertex Vee-Rings</u>	Up to 300 ⁰ C	Up to 28 Mpa (280 bar)	2 m/s	Up to 2 - 13	Air, gas, steam, water, oils and chemicals	Reciprocating equipment.
<u>Wave Packings</u>	120 ⁰ C	35 Mpa (350 bar)	2 m/s	5 - 9	Oil and water, compressed air, gases, mineral oil-based hydraulic fluids. Presses, earth-moving machinery, jacks fork-lift trucks.	Reiprocating and slow-oscillating.